



## ***Protouch Camera Support***

protouch  
*Vinten*

[www.vinten.com](http://www.vinten.com)

## Pro-5DC System

### Specification:

#### PH5 Pan & Tilt Head

Load Capacity:	6 kg / 13.3 lbs
Weight:	1.3 kg / 2.9 lbs
Tilt Range:	+90° to -60°
Pan Range:	360°
Camera Fixing:	Sliding quick release plate with 1/4" and 3/8" camera screws plus location pin
Levelling Bowl:	75mm
Levelling Bubble:	Standard
Pan Bar:	One

#### PT525 Two-Stage Aluminium Tripod

Load Capacity:	15 kg / 33 lbs
Weight:	3 kg / 6.6 lbs
Minimum Height:	32 cm / 12.6"
Maximum Height:	156 cm / 61.4"
Head Fixing:	75 mm bowl

#### PRO-5DC System

Weight:	7 kg / 15.4 lbs - includes head, tripod, spreader & soft case
---------	---



- **Lightweight Camera Support System**
- **Simple to set up**
- **Ideal for mini DV cameras**
- **Easy to transport**

**The Pro-5 system supports payloads up to 6kg/13.2lbs, ideal for the latest range of small, professional digital and ENG cameras.**

Providing smooth pan & tilt movement and outstanding stability, this low priced lightweight system offers the professional

control you'd expect from larger systems at a fraction of the cost.

The Pro-5DC system comprises the PH5 pan & tilt head, the PT525 two-stage aluminium tripod with enhanced adjustable leg locks, floor spreader and soft case.

## PD114 Dolly

### U005-103 - PD114 Dolly with Cableguards


Capacity:	40 kg / 88.2 lbs
Weight:	5.3 kg / 11.7 lbs
Base diameter:	112 cm / 44.1"
Wheel diameter:	12.5 cm / 5"

**The PD114 Dolly is available for use with the entire product range.**



## Pro-6 & Pro-10 Systems

- Professional Quality Camera Control
- Continuously Variable Fluid Drag
- Illuminated Levelling Bubble
- Exceptional rigidity



Includes illuminated levelling bubble

### Specification:

#### Type No: 3808-3 Pro-6 Pan & Tilt Head

Capacity:	6 kg / 13.2 lbs
Weight:	1.6 kg / 3.5 lbs
Tilt Range:	+90° -60°
Pan Range:	360°
Counterbalance:	Fixed for a 2.5 kg / 5.5 lb camera weight
Camera Fixing:	Sliding quick release plate (interchangeable with Vision 3 & Vision 6) with 3/8" and 1/4" screws with locating pin
Ball Base:	75mm
Levelling Bubble:	Illuminated
Pan Bar:	Single fixed length - optional second

### Specification:

#### Type No 3809-3 Pro-10 Pan & Tilt Head

Capacity:	10 kg / 22 lbs
Weight:	2.4 kg / 5.2 lbs
Tilt Range:	+90° -60°
Pan Range:	360°
Counterbalance:	Fixed for a 7.5kg / 16.5 lb camera weight
Camera Fixing:	Sliding quick release plate (interchangeable with Vision 3 & 6) with 3/8" and 1/4" screws with locating pin.
Ball Base:	75 mm
Levelling Bubble:	Illuminated
Pan Bar:	Single fixed length - optional second

### Specification:

#### Type No 3819-3 Pozi-Loc Two-Stage Tripod

Capacity:	25 kg / 55 lbs
Weight:	3.2 kg / 7lbs
Min Height:	41.6cm / 16.4"
Max Height:	156.2 cm / 61.5"
Transport Length:	71 cm / 28"
Head Fixing:	75 mm bowl

#### PRO-6DC System

Weight:	7.4 kg / 16.3 lbs - includes head, tripod, spreader & soft case
---------	---

#### PRO-10DC System

Weight:	8.2 kg / 18.1 lbs - includes head, tripod, spreader & soft case
---------	---



**The Pro-6 and Pro-10 are the two NEW lightweight, high performance pan & tilt heads from Vinten, perfect for supporting the latest range of small professional DV camcorders in corporate, industrial and event videography.**

Continuously variable fluid drag and a capacity of either 6kg or 10kg (13.2 or 22lbs) ensures that these lightweight heads provide smooth movement and complete camera control.

Designed to be simple to use the Pro-6 and Pro-10 incorporate easy to adjust drag knobs and are the ONLY heads in their class to include an illuminated

levelling bubble for quick and convenient set up in low light situations.

These two Protouch systems combine either the Pro-6 or Pro-10 lightweight heads with the Vinten Pozi-loc tripod. The outstanding rigidity and positive action clamping system has meant that the Pozi-Loc tripod is the preferred tripod for the camera operators worldwide for professional control of much greater payloads.

**Pro-6DC and Pro-10DC system packages include a two-stage black aluminium pozi-loc tripod, floor spreader and soft case.**

**When you buy Vinten you receive a FREE 2 year warranty as well as a global network of sales and service support.**

**Sales Offices:**

**Vinten Broadcast Limited**

Western Way  
Bury St Edmunds  
Suffolk IP33 3TB UK  
Telephone: +44 (0)1284 752121  
Facsimile: +44 (0)1284 750560  
Sales Office Fax: +44 (0)1284 757929

**Vinten Broadcast s.a.r.l.**

8-10, rue Séjourné  
94044 Créteil France  
Telephone: 01 45 13 18 75  
Facsimile: 01 43 77 15 08

**Vinten GmbH**

Gebäude 16  
Planiger Straße 34  
D-55543 Bad Kreuznach  
Telephone: +49 (0)671 483 43-30  
Facsimile: +49 (0)671 483 43-50

**Vinten Japan KK**

3-75-5 Sendagaya  
Shibuya-Ku  
Tokyo 151-0051 Japan  
Telephone: (03) 3 478 6017  
Facsimile: (03) 3 478 6018

**Vinten Inc.**

709 Executive Boulevard  
Valley Cottage, New York  
USA 10989-2011  
Telephone: (845) 268 0100  
Toll Free Sales: 1 888 2 VINTEN  
Facsimile: (845) 268 0113

**Vinten Asia Pacific Pte**

6 New Industrial Road  
#02-02 Hoe Huat Industrial building  
Singapore 536199  
Telephone: (65) 629 75 776  
Facsimile: (65) 629 75 778

**Vinten**

# Pozi-loc Tripod

**The NEW black aluminium Pozi-loc tripod is the most rigid in its class and is offered exclusively with the new Pro-6 and Pro-10 systems. Offering unrivalled torsional rigidity the Pozi-loc tripod doesn't compromise operational essentials such as weight, reliability, maintenance and speed of set up.**

**Why rigidity is important to your work.**

- The less movement in a support the better the drag system works and the smoother an on air move.
- The less rigid a support the more spring back at the end of a movement.
- The less rigid a support the more shake is evident in wind buffeting etc.

